

GENERAL SERIES BATTERY

General Series VRLA batteries are designed with AGM(Absorbent Glass Mat) technology, High performance plates and electrolyte to give extra power output for common power backup system. General Series Batteries are the general purpose batteries with 5 years floating design life at 25°C.

APPLICATION

- ☆ Emergency Power System
- ☆ Communication equipment
- ☆ Telecommunication systems
- ☆ Uninterruptible power supplies
- ☆ Electric toy car and wheelchairs, etc

GENERAL FEATURES

- ☆ Heavy Duty Grid
- ☆ Mechanized assembly
- ☆ Non-spillable construction
- ☆ High Reliability and Stability
- ☆ Sealed and Maintenance-free
- ☆ Long Life and low self-discharge design

SPECIFICATION

Battery Model	Nominal Voltage		6V	
	Rated capacity (20Hour rate)		7.5Ah	
	Cells Per battery		3	
Dimension	Length		Width	Height
	151mm		34mm	94mm
Approx Weight	1.15Kg			
Internal Resistance	Full charged at 25°C(77°F): Approx 18mΩ			
Max. discharge current	112.5A(5s)			
Floating design life @ 25°C (77°F)	5 years			
Capacity @ 25°C (77°F)	20Hour rate(0.375A/5.25V)	10Hour rate(0.68A/5.25V)	5Hour rate(1.08A/5.25V)	1Hour rate(2.48A/5.25V)
	7.5Ah	6.80Ah	5.42Ah	2.48Ah
Capacity affected by Temp(20 HR)	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C(5°F)
	102%	100%	85%	65%
Self Discharge @ 25°C (77°F)	After 3 months storage		After 6 months storage	
	91%		82%	
Charge method @ 25°C (77°F)	Cycle Use		7.24-7.45V (Max. charge current: 2.25A)	
	Float Use		6.80-6.90V	

3FM7.5/6Volt 7.5Ah




- ☆ Power tools
- ☆ Alarm system
- ☆ Marine equipment
- ☆ Medical equipment
- ☆ Fire and Security System

CONSTRUCTION

- ☆ Container: ABS(UL94-HB) / Flame Retardant ABS (UL94-V0)
- ☆ Negative: Lead
- ☆ Electrolyte: Sulfuric acid
- ☆ Safety Valve: EPDR
- ☆ Positive: Lead dioxide
- ☆ Separator: Fiber glass
- ☆ Terminal: Copper

OUTER DIMENSION (mm)



TERMINAL TYPE (mm)

CONSTANT CURRENT(AMP) AND CONSTANT POWER(WATT) DISCHARGE TABLE AT 25°C (77°F)

F.V / TIME		5min	10min	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h
4.80V	A	27.00	17.63	13.13	8.63	4.50	2.63	1.95	1.55	1.32	0.87	0.71	0.38
	W	143.10	93.59	70.22	46.58	24.53	14.31	10.73	8.53	7.24	4.82	3.95	2.15
5.10V	A	24.75	16.56	12.06	8.19	4.65	2.52	1.91	1.50	1.29	0.86	0.70	0.38
	W	134.89	91.92	67.25	46.05	26.16	14.23	10.81	8.51	7.32	4.85	3.95	2.15
5.25V	A	22.95	15.83	11.25	7.94	4.50	2.47	1.88	1.43	1.28	0.84	0.69	0.38
	W	126.24	89.02	63.56	45.24	25.65	14.13	10.73	8.19	7.33	4.85	3.97	2.16
5.40V	A	20.90	15.13	10.50	7.58	4.35	2.41	1.84	1.40	1.22	0.82	0.67	0.37
	W	114.95	86.21	60.11	43.75	25.12	13.90	10.66	8.16	7.10	4.79	3.91	2.13
5.55V	A	18.08	14.25	9.75	7.05	4.13	2.34	1.76	1.37	1.17	0.80	0.66	0.36
	W	102.12	82.29	56.55	41.24	24.13	13.71	10.35	8.11	6.88	4.72	3.87	2.10

3FM7.5/6Volt 7.5Ah


Discharge characteristic Curve



Charge Characteristic Curve For Standby Use



Cycle service life in relation to depth of discharge



Relationship Between Charging Voltage And Temperature




Temperature Effects On Capacity



Storage Characteristics



Effect Of emperature On Long Term Life



Charge Characteristic Curve For Standby Use

